



## Proven Protection Since 1977

Conklin's Rapid Roof III acrylic elastomeric roof coating has an impressive performance record dating back to 1977. It provides excellent protection against the elements, remains flexible to withstand building movement, and reduces cooling costs for significant energy savings. In fact, a reflective, ENERGY STAR-rated Rapid Roof coating delivers such substantial savings on heating and cooling bills that many building owners see a complete return on investment within the warranty period!

### Features

- 85% reflectivity with cool, white surface
- Completely seamless membrane for exceptional waterproofing
- Water-based formula for easy clean-up and environmental protection
- Durable, long-term performance
- Superior dirt resistance

Rapid Roof III is designed for use with the following Conklin Roofing Systems:

MR FABRIC FOAM  
SINGLE PLY RECOAT



# Rapid Roof III® – For Easy Application, Superior Protection

Rapid Roof III® is easily brushed, rolled, or sprayed over any approved new or retrofit roof deck, including metal, spray polyurethane foam, plywood, approved isocyanurate insulation board (ISO board), approved oriented strand board (OSB), asphalt built-up roofing and approved single-ply membranes.

## Testing and Approvals

Conklin is a member of National Roofing Contractors Association (NRCA), Spray Polyurethane Foam Alliance (SPFA), a division of the American Plastic Council, the EPA Energy Star® program and the Cool Roof Rating Council (CRRC). Our products meet or exceed the standards set by these organizations.



Conklin is a charter member of the Energy Star Program. Rapid Roof III meets the criteria established by EPA/DOE for energy efficiency and reflectivity.



Rapid Roof III meets the requirements of reflectivity and emissivity for inclusion in the CRRC program.



Rapid Roof III has achieved a UL-790 "Class A" Fire Rating, is approved in Florida State approval 7033, and meets the requirements of California's Title 24 building energy code.

## Specifications

<b>Elongation</b>	303% (base and top coats combined)	ASTM D-412
<b>Tensile Strength</b>	232 psi (base and top coats combined)	ASTM D-412
<b>Flexibility</b>	1/8" Mandrel Bend at -40 F	ASTM D-1737
<b>Fire Rating*</b>	UL-790 Class "A," combustibles and non-combustible decks	
<b>Standard Test Method for acrylic coatings used in roofing</b>	Pass	ASTM D-6083-97
<b>Solar Reflectivity</b>	85%	ASTM E-903
<b>Base Coat Thickness</b>	13.0 dry mils	
<b>Top Coat Thickness</b>	12.0 dry mils	
<b>Drying Time</b>	2-8 hours (depending on humidity, temperature, UV exposure and wind)*	

\*Refer to Underwriters Laboratories Roofing Materials and Systems directory for specific fire resistance assemblies or contact Conklin Roofing Systems.

## Top Coat Colors Offer Energy-Efficient Technology

Rapid Roof III top coat is available in standard white, light tan, and light gray. Rapid Roof III's top coat colors utilize "cool pigment" technology so that they meet ENERGY STAR guidelines for energy efficiency.

## Optional Warranties

We extend our optional warranty program on your new Conklin Roofing System with confidence. Limited material and manufacturer-backed labor and materials warranties of up to ten years are available. Contact your Conklin independent roofing contractor for more information.

For more information, contact:



(612) 750-6639 Mobile Office

(800) 435-8547 Toll Free

[www.skylinecbs.com](http://www.skylinecbs.com)

[info@skylinecbs.com](mailto:info@skylinecbs.com)

