

Conklin Durability Meets Cool-Weather Technology

When the weather gets too cool for typical acrylic coatings, Equinox® lets you restore your roof in spring, summer or fall. One of the first low-temperature acrylic coatings on the market, Equinox is specially formulated to form a strong film in cool weather, so it dries quickly in early spring and late fall.

Equinox forms a completely seamless membrane for excellent protection from the elements and the flexibility to withstand building movement. It also provides a reflective top coat that keeps the roof cooler, resulting in tremendous energy savings for the building owner.

Features

- Easy application at temperatures 36 °F and rising
- Provides a cool, reflective top coat (reflectivity in testing)
- · Completely seamless membrane for exceptional waterproofing
- · Water-based formula for easy clean-up
- Low VOC emissions to help protect the environment
- Requires about 20 percent less coating, saving even more money!

Equinox is formulated for use with the following Conklin Roofing Systems:

EPDM MR FABRIC FOAM

Equinox — For Easy Application, Superior Protection

Equinox may be sprayed or rolled over approved new or retrofit roof deck, including metal, sprayed polyurethane foam, exterior plywood, and approved isocyanurate insulation board.

Testing and Approvals



Conklin is a charter member of the Energy Star Program. Equinox meets the test criteria established by EPA/DOE for energy efficiency and reflectivity.



Equinox meets the requirements of reflectivity and emissivity for inclusion in the CRRC program.

Specifications

• • • • • • • • • • • • • • • • • • • •		
Elongation	250% (base and top coats combined)	ASTM D-412
Tensile Strength	232 psi (base and top coats combined)	ASTM D-412
Flexibility	½" Mandrel Bend at –40 F	ASTM D-1737
Fire Rating*	UL-790 Class "A," combustible and	
	non-combustible decks	
Standard Test Method for acrylic coatings used in roofing	Pass	ASTM D-6083-97
Solar Reflectivity	85%	ASTM E-903
Base Coat Thickness	13.0 dry mils	
Top Coat Thickness	12.0 dry mils	
Drying Time	1-3 hours (depending on humidity, temperature, UV exposure and wind)*	

^{*}Refer to Underwriters Laboratories Roofing Materials and Systems directory for specific fire resistance assemblies or contact Conklin Roofing Systems.

Optional Warranty Program

We extend with confidence our optional Warranty Programs for your new Conklin Roofing System. Either a limited materials warranty or a manufacturer-backed labor and materials warranty of up to 15 years are available. Contact your Conklin roofing contractor for more information.

For more information, contact:



(612) 750-6639 Mobile Office (800) 435-8547 Toll Free

www.skylinecbs.com info@skylinecbs.com

